



DATA SHEET

AFL SUN LED 30W 3K white

Order description

Item number


GTIN

AFL SUN LED 30W 3 K WH

EL10810121

4015120810121





Product description

- LED floodlight with high-grade die-cast aluminium housing and integrated motion detector with 160° field of detection for convenient lighting control
- 30 W LED luminous efficiency corresponds to 139 W light bulb, light colour approx. 3000 K white
- High light yield of 80 lm/W, excellent colour rendering index Ra 80

Technical data

GENERAL		
Conformity	CE, RoHS, WEEE	
warranty	3-year	
MOUNTING		
Installation type	Surface mounting	
Mounting location	Wall	
HOUSING		
Dimensions	Length 290 mm x Width 227 mm x Height/ Depth 86 mm	
Weight	1880 g	
Material	Aluminium and UV-stabilised plastic	
Protection type	IP 65	
Permissible ambient temperature	-25 °C+40 °C	
Colour	white, similar to RAL 9016	
Terminal	2,5 mm² / 1,5 mm²	
ELECTRICAL VERSION		
Protection class	1	
Nominal voltage	230 - 230 V / 50 Hz	
Stand-by consumption	0.5 W	
	0.5 W	

transparent	
direkt	
110 °	
<20 %	
28 W	
3370 lm	
120 lm/W	
L80B50 = 50.000 h	
3000 K	
> 80	
A++ to A	
160°	
12 m	
50 m²	
mechanically with included cut to size lens mask	
2,5 m	
4 m	
10	





DATA SHEET

AFL SUN LED 30W 3K white

Order description Item number


AFL SUN LED 30W 3 K WH EL10810121 4015120810121

Accessories


Product designation	Item number	GTIN
Wall Arm 700 WH	EL10810527	4015120810527
Ground Spike WH	EL10810541	4015120810541

GTIN

Scale drawing




Field of detection



- Head-on to detector
- Passage area / diagonally to detector

Light distribution



Energy Conservation Solutions Pty Ltd

Exclusive Distributor for **ESYLUX** in Australia Locations: VIC/TAS, NSW, QLD, ACT, SA/NT & WA Phone: **1300 306 136**

For contact details visit: www.ecs.net.au